

# DINITROL 353

## Spray

Body Repair

Body Repair

### Characteristics:

DINITROL 353 Spray is a synthesis of polymers with high-pressure and wear-resistance (PTFE) additives and viscosity agents. DINITROL 353 Spray is a guaranteed non-toxic product without metallic salts. It is splash water-resistant and withstands vapour from dissolved products. It is extremely resistant to compression and capable of creep.

### Areas of Application:

DINITROL 353 Spray is an ideal lubricant for all devices which are vulnerable to water or operate under water.

DINITROL 353 Spray is used to lubricate chains, for systems in the food industry, in the canned food and sugar industry, in the paper industry, in the Navy, in civil engineering and the vehicle sector.

### Technical data:

Colour:	Yellowish/ transparent
Density:	0.66 g/cm <sup>3</sup>
Propellant:	Propane/butane
Resistant to:	Weak acids and alkalis
Best stability in temperature range:	- 30°C to + 200°C
Storage time:	24 months (cool and dry)
Package size:	500 ml spray can

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH  
Pyrmonter Str. 76  
D-32676 Lügde  
Telephone:  
+49 (0) 52 81 / 9 82 98-0  
Fax:  
+49 (0) 52 81 / 9 82 98-60  
Email:  
service@dinol.com