

DINITROL MS 40 Spray

Characteristics:

DINITROL MS-40 is a multi-functional spray for many different applications. The product is a non greasy lubricant which is water repellent and water displacing. DINITROL MS-40 is free of silicones and is not harmful to most plastics, lacquers and rubber.

DINITROL MS-40 protects metal surfaces like steel, aluminium, copper, brass, silver, tin and lead from corrosion, water, dirt and finger prints.

DINITROL MS-40 penetrates rust to release seized screws or hinges and frozen metal parts.

DINITROL MS-40 lubricates all kind of moving parts. It stops screeching immediately.

DINITROL MS-40 cleans metal surfaces from grease, tar, grime. It dissolves adhesives and easily removes labels and adhesives tapes.

Application:

DINITROL MS-40 is used for many ranges of application like the automotive industry, in industrial environments, but also for arms, ignition systems, tools and processing machinery, and also for the naval and construction industry.

Technical data:

Colour:	clear yellowish
Density (at 23°C):	0,74 g/cm ³
Flash point:	- 10°C
Propellant:	propane / butane
Solubility in water:	water-soluble
Shelf life:	24 months
Storage:	cool and dry
Package size:	400 ml spray can

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Telephone:
+49 (0) 52 81 / 9 82 98-0
Fax:
+49 (0) 52 81 / 9 82 98-60
Email:
service@dinol.com