

Printing date 20.11.2010 Revision: 20.11.2010

1 Identification of the substance/mixture and of the company/undertaking

· Product details

· Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

· Application of the substance / the preparation Lacquer

· Manufacturer/Supplier:

Dinol GmbH

Pyrmonter Strasse 76

D-32676 Lügde

Tel: +49 5281 9829 80 *Fax:* +49 5281 9829 860

E-mail: thomas.suerig @dinol.com

- · Further information obtainable from: Research & Development
- · Information in case of emergency: Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC

×

Xi; Irritant

R36: Irritating to eyes.

F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xi Irritant

F+ *Extremely flammable*

· Risk phrases:

12 Extremely flammable.

- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Safety phrases:
- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.

(Contd. on page 2)



Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

(Contd. of page 1)

23 Do not breathe fumes/aerosol.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· Classification in accordance with Directive 75/324/EEC: Extremely flammable

3 Composition/information on ingredients

- · Chemical characterization
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 141-78-6 EINECS: 205-500-4	Ethyl acetate	Xi R36;	10-<25%
CAS: 74-98-6 EINECS: 200-827-9	Propane liquefied	▶ F+ R12	10-<25%
CAS: 106-97-8 EINECS: 203-448-7	Butane, pure	▶ F+ R12	10-<25%
CAS: 123-86-4 EINECS: 204-658-1	n-Butyl acetate	R10-66-67	10-<25%
CAS: 108-10-1 EINECS: 203-550-1	4-Methylpentan-2-one	Xn R20; Xi R36/37; → F R11 R66	10-<25%
CAS: 67-64-1 EINECS: 200-662-2	Acetone	Xi R36;	10-<25%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene, mixed isomers, pure	Xn R20/21; Xi R38 R10	5-<10%
CAS: 9004-70-0	Cellulose nitrate	ĕ F R11	1-<5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor:
- · The following symptoms may occur:

Headache

Dizziness

· Treatment If swallowed or in case of vomiting, danger of entering the lungs.

- G



Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

(Contd. of page 2)

:

5 Firefighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· Special hazards caused by the substance, its products of combustion or resulting gases:

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

*

6 Accidental release measures

· Person-related safety precautions:

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

· Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Measures for cleaning/collecting:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Additional information: See Section 13 for disposal information.

¥

7 Handling and storage

- · Handling:
- · Information for safe handling:

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

(Contd. of page 3)

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:		
141-7	8-6 Ethyl acetate	
WEL	Short-term value: 400 ppm	
	Long-term value: 200 ppm	
106-97-8 Butane, pure		
WEL	Short-term value: 1810 mg/m³, 750 ppm	
	Long-term value: 1450 mg/m³, 600 ppm	
	Carc (if more than 0.1% of buta-1.3-diene)	
123-86-4 n-Butyl acetate		
WEL	Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m³, 150 ppm	

108-10-1 4-Methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 Xylene, mixed isomers, pure

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- · Protection of hands: Protective gloves and protective skin cream
- · Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials: Strong material gloves

(Contd. on page 5)

(Contd. of page 4)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

· Eye protection:

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· General Information

· Appearance:

Form: Aerosol
Colour: Dark grey
Odour: Ester-like

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

• Flash point: $< -10^{\circ}C (DIN 53213)$

• Ignition temperature: 365°C

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

· Explosion limits:

 Lower:
 1.5 Vol %

 Upper:
 13.0 Vol %

· Vapour pressure At 20°C: 3600 hPa

• Density At 20°C: 0.78 g/cm^3

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Solvent content:

Organic solvents: 81.3 %

Solids content: 15.8 % (DIN 53216)

· Additional information:

 VOC (EU):
 82.00 %

 VOC (EU):
 640.0 g/l

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

GB



Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

(Contd. of page 5)

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

*

12 Ecological information

- · Information about elimination (persistence and degradability):
- · Other information: There is no data available for the product.
- · Ecotoxical effects:
- · Remark: There is no data available for the product.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

*

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
	COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND
	PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST

16 05 00 gases in pressure containers and discarded chemicals

16 05 04 gases in pressure containers (including halons) containing dangerous substances

15 00 00 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00 packaging (including separately collected municipal packaging waste)

15 01 10 packaging containing residues of or contaminated by dangerous substances

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

GB



Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

(Contd. of page 6)

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 2 5F Gases.

· Danger code (Kemler): · UN-Number: 1950
· Packaging group: · Hazard label 2.1

· Description of goods: 1950 AEROSOLS

Limited quantities (LQ) LQ2
 Transport category 2
 Tunnel restriction code D

· Maritime transport IMDG:



· IMDG Class: 2.1 · UN Number: 1950 · Label 2.1 · Packaging group: -

EMS Number: F-D,S-U
Marine pollutant: No
Proper shipping name: AEROSOLS

- - - -

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 2.1 · UN/ID Number: 1950 · Label 2.1 · Packaging group: -

· Proper shipping name: AEROSOLS, flammable

15 Regulatory information

- · Chemical safety assessment A Chemical Safety Assessment has not been carried out.
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

(Contd. on page 8)



Printing date 20.11.2010 Revision: 20.11.2010

Trade name: Dinitrol 8020 Kunststofflack Spray dunkelgrau

(Contd. of page 7)

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R36 Irritating to eyes.
- R36/37 Irritating to eyes and respiratory system.
- R38 Irritating to skin.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Research & Development
- · Contact: Dr. Thomas Sürig
- * * Data compared to the previous version altered.

GB ·