

DINITROL 588

Pump cleaning and preservation compound

Characteristics:

DINITROL 588 is a compound of polyurethane compatible softeners and additives, which avoids the curing of polyurethane residues. DINITROL 588 can be used also for cleaning and long term preservation of pumping equipments which are used for humidity curing materials, like polyurethanes, silane terminated polymers, etc.

Applications:

Clean the follower plate of the pump mechanically and with suitable solvent.

Apply DINITROL 588 in for the equipment standard packaging, e.g. 20, or 50 Liter pail.

Start the pump, bring it into operational mode and flush the system with DINITROL 588, until the cleaning compound comes out without any discolourations.

Shut the unit off and let stay, until next usage. Start up then in same way, as when applying DINITROL 588.

IMPORTANT: Make sure, to flush the pump with the material to be in use, until all residuals of DINITROL 588 are flushed out and can not disturb the properties of the bond.

Technical Data:

Colour:	Orange
Density:	~ 1.396 g/ml
Flash point:	101°C
Processing temperature:	+ 0°C to + 35°C
Dynamic viscosity at a temperature of + 20°C	10000 mPas
Package size:	20 and 50 Liter pails, other upon request
Storage time:	between 0°C and 35°C 24 months

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmont Str. 76
D-32676 Lügde
Telefon:
+49 (0) 52 81 / 9 82 98-0
Telex:
+49 (0) 52 81 / 9 82 98-60
E-Mail:
service@dinol.com